



D-Line Display

Signage Solutions

50"

4K UHD

500cd/m²



50BDL4650D

Smart and modular for an even longer lifetime powered by Android

Philips D-Line is designed to engage your audience and delight customers. Powered by Android 11 for easy software integrations, this versatile display is suitable for impact in any setting.

Innovative solutions for any signage application

- Save and play content with internal memory
- Android SoC processor. Native and web apps
- Integrated WiFi 6 and Bluetooth module

Care about you, your business and your audience

- 4G/LTE optional module for reliable connection
- Modularity longer product lifetime
- FailOver. Ensure your display never goes blank

Maximizing the impact of your message

- Connect and control your content via the cloud
- Catch the Wave for revolutionary results

D-Line Display 50BDL4650D/11

Highlights

Internal Memory



Save and play content with internal memory. Upload your media into the display and playback content immediately. Working in conjunction with the internal browser, it also serves as a memory cache when streaming online content. If the network ever fails, the internal memory keeps content running by playing a cached version of the content, ensuring that your media stays up even if the network goes down.

FailOver

Critical for demanding commercial applications, FailOver is a revolutionary technology that automatically plays back-up content on screen in the unlikely event of a media player failure. Simply select a primary input connection and a FailOver connection and you are ready for instant content protection.

Modularity

Extend your display into the future with our modular approach. Bringing opportunities for longer product lifetime with easily detached and replaced components, and a firm focus on sustainability, with reduced WEEE disposal.

Powered by Android 11

Powered by Android 11 and with integrated WiFi, your Philips D-Line delivers the ultimate, most secure and connected display experience. Optimised for native Android apps, and enabling you to install web apps and software directly onto the display, eliminating the need for an external media player.

SmartBrowser

Connect and control your content via the cloud with our integrated HTML5, Chromium-based browser. Design your content online and connect a single display, or your entire network, either landscape or portrait, in 4k UHD resolution. Simply connect to the internet via WiFi or with an RJ45 cable.

PPDS Wave

Unlock the power, versatility and intelligence inside your Philips D-Line displays remotely with Wave. This evolutionary cloud platform puts you fully in control, with simplified installation and set-up, monitoring and controlling displays, upgrading firmware, managing playlists and setting power schedules. Saving you time, energy and environmental impact.



D-Line Display 50BDL4650D/11

Specifications

Picture/Display

Diagonal screen size (metric): 125.7 cm Diagonal screen size (inch): 49.5 inch

Aspect ratio: 16:9

Panel resolution: 3840 x 2160 Pixel pitch: 0.2854 x0.2854 mm

Optimum resolution: 3840 x 2160 @ 60Hz

Brightness: 500 cd/m² Display colors: 1.07 Billion Contrast ratio (typical): 4000:1 Dynamic contrast ratio: 500,000:1 Response time (typical): 8 ms Viewing angle (horizontal): 178 degree

Viewing angle (vertical): 178 degree

Panel technology: VA Operating system: Android 11

Haze: 25%

Connectivity

Audio output: 3.5mm jack

Video input: DVI-I (x 1), DisplayPort 1.4 (x1), HDMI 2.0 (x2), USB 3.0 (x2), VGA (via DVI)

Audio input: 3.5 mm jack

Other connections: Micro USB (x1) (OTG)

Video output: DisplayPort 1.4 (x1)

External control: RJ45, RS232C (in/out) 2.5 mm jack, IR (in/out) 3.5 mm jack

WiFi: WiFi 6 + Bluetooth 5.2 (slide-in module)

Convenience

Placement: Landscape (24/7), Portrait (24/7)

Tiled Matrix: Up to 10 x 15 Screen saving functions: Pixel Shift Keyboard control: Hidden, Lockable Signal loop through: RS232, IR Loopthrough,

DisplayPort

Energy saving functions: Smart Power Network controllable: RS232, RJ45, WiFi WiFi protocol: a b g n, 802.11 ax, 802.11 ac

Built-in speakers: 2 x 10W RMS

Mains power: 100 ~ 240 VAC, 50 ~ 60 Hz

Consumption (Typical): 75 W Consumption (Max): 126 W

Standby power consumption: <0.5 W

Supported Display Resolution

Computer formats: 1920 x 1080, 60Hz, 1024 x 768, 60Hz, 1280 x 1024, 60Hz, 1280 x 720, 60Hz, 1440 x 900, 60 Hz, 1600 x 900, 60Hz, 1680 x 1050, 60Hz, 3840 x 2160, 30, 60Hz, 640 x 480,

60Hz, 800 x 600, 60Hz

Video formats: 1080i, 50, 60Hz, 576i, 50Hz, 576p, 50Hz, 480p, 60Hz, 480i, 60Hz, 1080p, 50, 60Hz,

720p, 50,60 Hz, 2160p, 50, 60Hz

Dimensions

Set Width: 1128.4 mm Product weight: 14.6 kg Set Height: 649.0 mm Set Depth: 63.5 mm Set Width (inch): 44.43 inch Set Height (inch): 25.55 inch

Wall Mount: 400 (H)x 400 (V) mm, M6

Set Depth (inch): 2.50 inch Bezel width: 14.9 mm (Even bezel) Product weight (lb): 32.19 lb

Operating conditions

Altitude: 0 ~ 3000 m

Temperature range (operation): 0 ~ 40 °C

MTBF: 50,000 hour(s)

Temperature range (storage): -20 ~ 60 °C Humidity range (operation)[RH]: 20 - 80% RH

(No condensation)

Humidity range (storage) [RH]: 5 - 95% RH (No

condensation)

Multimedia Applications

USB Playback Video: MPEG, H.263, H.264, H.265, AVI, MP4, MPEG4, VP8, VP9, WEBM USB Playback Picture: BMP, JPEG, PNG USB Playback Audio: AAC, HEAAC, MPEG

Internal Player

CPU: 2x A72 + 4x A53 GPU: ARM Mali-T860 MP4 Memory: 4GB RAM Storage: 32 GB eMMc

Accessories

Included Accessories: RS232 daisy chain cable(1.8m)(x1), Philips logo (x1), AC Switch Cover, USB cover and screws, Warranty card (x1), Power cable (3m), IR sensor cable (1.8 m) (x1), Quick start guide, Remote control & AAA batteries, RS232 Cable (3m), WiFi module, Cable clip (x2), HDMI cable (1.8 m) (x1)

Miscellaneous

On-Screen Display Languages: English, French, German, Spanish, Polish, Turkish, Russian, Italian, Simplified Chinese, Traditional Chinese, Arabic, Japanese, Danish, Dutch, Finnish, Norwegian,

Portuguese, Swedish Warranty: 3 year warranty

Regulatory approvals: CE, CCC, RoHs 2, CB, EMF,

FCC, Class A, UL, VCCI, J-Moss, PSE

© 2025 Koninklijke Philips N.V. All Rights reserved

Issue date 2025-02-06 Version: 4.4.1

EAN: 87 12581 80555 5

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.



www.philips.com