



Signage 4050 Series



32BDL4050Q

Philips Signage 4050 Series

Efficiency made easy – your versatile 24/7 display

Inform and enthral with Philips Signage 4050. FHD resolution is matched with enhanced brightness and high haze, and the efficiency of the tried and tested Android 10 SoC. Wave-ready for remote management, putting you in full control.

Easy operation

- Remote management with Philips Wave
- Add optional Philips ScreenShare

Energy Star compliant. EPEAT rating in progress

• Supporting business sustainability and energy savings.

24/7 operation

- 400 cd/m2 brightness
- Higher haze rate for better visibility
- Easily mounted in landscape or portrait.

Plug and play with Android 10

• Proven reliability. No need for external media player.

Signage 4050 Series 32BDL4050Q/00

Highlights

24/7 operation

With 400 cd/m2 brightness for better visibility, the Philips Signage 4050 display is designed to be used 24/7, making it a great selection for travel and transportation hubs, retail centres, food and beverage locations, and more. FailOver is also included enabling your display to switch automatically between primary and secondary inputs should an outage occur.

Versatile orientation

Install in portrait or landscape orientations, with size variants to suit a range of installation purposes across the range of settings and industries.

Plug and play with Android 10

Tried, tested, and proven intuitive user experience, with a professional Android 10 SoC built in for easy apps and solutions integrations and no need for an external media player.

Wave ready

Manage your display and control content remotely with Philips Wave Controller – your evolutionary ecosystem designed to support time, energy and cost efficiencies. Discover software applications to support your interactive vision from our network of proven partners on the PPDS ProStore.

Wireless screen sharing

Add in the fully secure and GDPR-compliant optional Philips ScreenShare presentation software for instant and effortless content sharing, using any device, on any network, and without additional hardware.

Energy Star compliant. EPEAT rating

Supporting business sustainability and energy savings, with power saving features and using more environmentally friendly materials on the product and in the packaging.

Signage 4050 Series 32BDL4050Q/00

Specifications

Picture/Display

Diagonal screen size (metric): 80 cm Diagonal screen size (inch): 31.5 inch

Aspect ratio: 16:9

Panel resolution: 1920x1080p Pixel pitch: 0.36375 x 0.36375 mm Optimum resolution: 1920 x 1080 @ 60 Hz

Brightness: 400 cd/m² Display colors: 16.7 Million Contrast ratio (typical): 1200:1 Dynamic contrast ratio: 500,000:1 Response time (typical): 8 ms

Viewing angle (horizontal): 178 degree Viewing angle (vertical): 178 degree

Picture enhancement: 3/2 - 2/2 motion pull down, Dynamic contrast enhancement, Progressive scan

Panel technology: ADS Operating system: Android 10

Haze: 25%

Connectivity

Audio output: 3.5mm jack

Video input: HDMI 2.0 (x2), USB 2.0 (x2), DVI-I (x 1),

USB 3.0 (x2)

Audio input: 3.5 mm jack Other connections: micro SD

External control: RJ45, RS232C (in/out) 2.5 mm

jack, IR (in/out) 3.5 mm jack

Convenience

Placement: Landscape (24/7), Portrait (24/7)

Tiled Matrix: Up to 3 x 3

Keyboard control: Lockable, Hidden Remote control signal: Lockable

Signal loop through: RS232, IR Loopthrough **Energy saving functions: Smart Power** Network controllable: RS232, RJ45

Sound

Built-in speakers: 2 x 10W RMS

Power

Mains power: 100 - 240V~, 50-60Hz, 1.5A Standby power consumption: <0.5 W **Power Saving Features: Smart Power**

Energy Label Class: G

Supported Display Resolution

Computer formats: 720 x 400, 70Hz, 640 x 480, 60,67,75Hz, 800 x 600, 60Hz, 832 x 624, 75Hz, 1024 x 768, 60Hz, 1152 x 870, 75Hz, 1280 x 720, 60Hz, 1920 x 1080, 60Hz, 1680 x 1050, 60Hz, 3840 x 2160, 30, 60Hz

Video formats: 480i, 60Hz, 480p, 60Hz, 576p, 50Hz, 576i, 50Hz, 720p, 50, 60Hz, 1080i, 50, 60Hz, 1080p, 50, 60Hz, 3840 x 2160, 30, 60Hz

Dimensions

Set Width: 726.5 mm Product weight: 5.7 kg Set Height: 425.4 mm

Set Depth: 69.1(D@Handle) / 65.1(D@Wall

mount) mm

Set Width (inch): 28.6 inch Set Height (inch): 16.75 inch

Wall Mount: 100 mm x 100 mm, 200 mm x 200

Set Depth (inch): 2.72 (D@Handle) / 2.56

(D@Wall mount inch

Bezel width: 11.9 mm (L/R/T) 17.2 (B) Product weight (lb): 12.57 lb

Operating conditions

Altitude: 0 ~ 3000 m

Temperature range (operation): 0 ~ 40 °C

MTBF: 50,000 hour(s)

Temperature range (storage): -20 ~ 60 °C Humidity range (operation)[RH]: 20 ~ 80% RH

(No condensation)

Humidity range (storage) [RH]: 5 ~ 95% RH (No

condensation)

Multimedia Applications

USB Playback Video: MPEG 1/2 (1080p 60Hz), MPEG 4 (1080p 60Hz), H.263 (1080p 60Hz), H.264 (4K2K 60Hz), H.265 (4K2K 60Hz), VP8

(1080p 60Hz), VP9 (4K2K 60Hz)

USB Playback Picture: JPEG, PNG, BMP, WEBP USB Playback Audio: AAC, HEAAC, MPEG 1/2/2.5 Layer 3, MPEG 1/2 Layer 1, MPEG 1/2 Layer 2

Internal Player

CPU: Quad Core Cortex A55

GPU: G52 MC1

Memory: 16GB, 3GB DDR

© 2025 Koninkliike Philips N.V. All Rights reserved.

Issue date 2025-03-17 Version: 14.14.1

FAN: 87 21038 10170 6

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

www.philips.com



Accessories

Included Accessories: RS232 daisy-chain cable, Philips logo (x1), AC Power Cord, Quick start guide, Remote control & AAA batteries, RS232 cable, USB cover and screws

Miscellaneous

On-Screen Display Languages: English, French, German, Italian, Polish, Turkish, Russian, Simplified Chinese, Spanish, Traditional Chinese, Arabic, Japanese

Warranty: 3 year warranty

Regulatory approvals: CB, CE, FCC, Class A, VCCI, RoHS, UL