



Collaboration Display

Signage Solutions

75"

Powered by Android

Multi-touch



75BDL4252E

Interactive display

Featuring multi-touch technology

This interactive display, powered by Android 14, has up to 50 touchpoints, maximising engagement and collaboration. Toughened anti-glare, anti-reflection and anti-fingerprint glass are ideal for heavy daily use in busy environments.

Smart and powerful

- OPS slot allows PC embedding without cabling
- EDLA certified display and Android 14
- Philips Wave-ready for remote display management and control
- Built-in ambient light sensor

Style and safety built in

- Cast directly from any device
- Anti-glare and anti-reflection toughened glass 7 MOH
- Palm rejection
- Blue light filter

Interactive and collaborative

- Wireless presentations
- Embedded microphones
- Multi-touch technology capable of 50 touchpoints
- Advanced IR touch and whiteboard application.

Signage Solutions

Collaboration Display

Highlights

OPS slot

Integrate a full-power PC or Android-powered CRD module directly into your Philips Professional Display. The OPS slot contains all of the connections you need to run your slot-in solution, including a power supply.

EDLA certified

Improved user experience and students' engagement, security and app integration are all part of the service. Directly benefit from Google apps and services natively, including Google Classroom, Docs and Slides, and seamlessly integrate Chromebooks and other Androidnative devices for simpler and more intuitive teaching and learning.

Philips Wave-ready

Your Philips Wave-ready display enables you to manage and maintain this device remotely, wherever you are, whenever you choose. This evolutionary cloud platform puts you in full control, with simplified installation and setup, monitoring and controlling displays, upgrading firmware, managing central content needs and setting power schedules. Saving you time, energy and environmental impact.

Built-in ambient light sensor

Built-in ambient light sensors contribute to energy savings by automatically adjusting the screen brightness to the surrounding lighting conditions.

Cast directly from any device

Teachers, students or employees can cast directly from their device with AirPlay, Google Cast and Miracast.

Anti-glare and anti-reflection toughened glass 7 MOH

Anti-glare, anti-reflection, anti-fingerprint coatings, 7 MoH hardness.

Blue light filter

Blue light filter to help protect eyes and avoid eye fatigue.

Palm rejection

Palm rejection for enhanced precision.

Wireless presentations

Philips ScreenShare makes it easy for teachers and students to wirelessly share their screens from their own device, whatever the operating system, via the browser or their favourite apps, onto the Philips Collaboration display.

Multi-touch technology

Create a memorable interactive experience with up to 50 touchpoints at the same time for slick, agile lessons or brainstorming sessions. Perfect for collaborative and co-creation applications, this display connects your audience with any content. Offering enhanced user friendliness with eraser functionality, palm rejection and tip size recognition.

Advanced IR touch and whiteboard application.

Advanced 0 gap IR touch with smaller, shallower bezels. The embedded whiteboard application enables seamless collaboration and brainstorming directly on the display.

75BDL4252E/00

Signage Solutions

Collaboration Display

Specifications

Picture/Display

Diagonal screen size (metric): 190.5 cm Diagonal screen size (inch): 75 inch Aspect ratio: 16:9 Panel resolution: 3840 x 2160 Pixel pitch: 0.4296 x 0.4296 mm Optimum resolution: 3840 x 2160 @ 60 Hz Brightness: 400 cd/m² Display colours: 1.07 billion Contrast ratio (typical): 1200:1 Dynamic contrast ratio: 500,000:1 Response time (typical): 8 ms Viewing angle (horizontal): 178 degree Viewing angle (vertical): 178 degree Picture enhancement: 3/2 - 2/2 motion pull down, 3D Combfilter, Motion compens. deinterlacing, Progressive scan, 3D MA deinterlacing, Dynamic contrast enhancement Panel technology: ADS **Operating system:** Android 14 OS UI resolution: 3840 x 2160 @ 60 Hz

Connectivity

Audio output: 3.5 mm Mini Jack (x 1), SPDIF digital audio out (1 x) Video input: HDMI 2.0 (x 3), USB 3.0 (x 4), USB-C (up to 65 W), USB-C Audio input: 3.5 mm mini jack (x 1), Display port Other connections: OPS, USB-B (x 2) Video output: HDMI 2.0 (x 1), VGA External control: RS232C (in/out) D-Sub9, Gb LAN x 2 Bluetooth: 5.2 BLE

Convenience

Placement: Landscape (18/7) Screen-saving functions: Pixel Shift, Low Brightness Keyboard control: Lockable Remote control signal: Lockable Signal loop through: RS232, IR Loop through Other convenience: Carrying handles, NFC, Bluetooth Network controllable: RS232, RJ45

Sound

Built-in speakers: 2 x 20 W

Power

Mains power: 100 ~ 240 VAC, 50/60 Hz Consumption (Typical): 130 W Standby power consumption: <0.5 W Power Saving Features: Smart Power Energy Label Class: F

Supported Display Resolution

Computer formats: 800 x 600, 56, 60, 72, 75 Hz, 848 x 480, 60 Hz, 1024 x 768, 60, 70, 75, 85 Hz, 1152 x 864, 75 Hz, 1280 x 960, 60, 85 Hz, 1280 x 1024, 60, 67, 75 Hz, 1360 x 768, 60 Hz, 1366 x 768, 60 Hz, 1600 x 1200, 60 Hz, 1920 x 1080, 60 Hz, 1920 x 1200, 60 Hz, 3840 x 2160, 24, 25, 30, 60 Hz

Video formats: 480p, 60 Hz, 720p, 50, 60 Hz, 1080i, 50, 60 Hz, 1080p, 50, 60 Hz, 2160p, 50, 60 Hz, 480i, 60 Hz

Dimensions

Set Width: 1709.4 mm Set Height: 1031 mm Set Depth: 97.3 mm Set Width (inch): 67.30 inch Set Height (inch): 41.30 inch Wall Mount: 800 x 400 mm, M8 Set Depth (inch): 3.83 inch Bezel width: 17.3 mm (T), 16.4 mm (R/L), 44.9 mm (B)

Weight

Product with packaging (kg): 55 kg Product with packaging (lb): 121.25 lb Product without stand (kg): 39.5 kg Product without stand (lb): 87.1 lb

Operating conditions

Altitude: 0 ~ 3000 m Temperature range (operation): 0 ~ 40 °C MTBF: 50,000 hour(s) Temperature range (storage): -20 ~ 60 °C Humidity range (operation)[RH]: 10–90% (without condensation) Humidity range (storage) [RH]: 10–90% (without condensation)

Multimedia Applications

USB Playback Video: H.263, H.264, H.265, MPEG1/2, MPEG4, VP8, VP9 USB Playback Picture: BMP, JPEG, PNG, WEBP USB Playback Audio: AAC, HEAAC, MPEG

Internal Player

75BDL4252E/00

CPU: 4 x A73 + 4 x A53 GPU: Multi-Core Mali-G52 Memory: 8 GB Storage: 128 GB eMMc Wi-Fi: 2T/2R 2.4/5/6 GHz

Accessories

Included Accessories: Cleaning cloth (x 1), AC Power Cord, Philips logo (x 1), Quick start guide (x 1), Remote control and AAA batteries, USB A to B cable (3 m) (x 1), AC switch cover and Screw x 1, HDMI cable (1.8 m) (x 1), Touch Pen (x 2) Optional accessories: Pen tray with 2 x colour stylus

Miscellaneous

On-Screen Display Languages: Arabic, Dutch, Danish, English, French, Finnish, German, Italian, Japanese, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Simplified Chinese, Turkish, Traditional Chinese Warranty: 5-year warranty Regulatory approvals: CE, FCC, Class A, RoHS, CB, EAC, EMF, ETL

Interactivity

Multi-touch technology: 0-gap Infrared touch Touchpoints: 50 simultaneous touch points Plug and play: HID compliant Protection glass: Anti-Glare, Blue light filter, Tempered safety glass 7 MOHS Built-in Microphone

© 2025 Koninklijke Philips N.V. All Rights reserved. Issue date 2025-06-12 Version: 9.9.1

EAN: 87 21038 10198 0



Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

www.philips.com