

PHILIPS



LED Display

Signage Solutions

31"

Direct View LED



31BDL7324L

Unleash your imagination even more

LED Display for every form and shape

No limits. No boundaries. Philips L-Line 7000 series is an LED signage solution for endless possibilities in shape and size. Seamless linking and multiple size options enable truly unique displays of any dimension for perfect results.

Next level performance

- Dynamic Panel Connect
- Factory calibrated
- Philips Active Health Monitoring

Endless possibilities

- Available in 3 dimensions
- Dynamic Power Saving
- Optional bevelled corners allow curved displays
- Seamless linking for perfect imagery

Ready for impact

- Conformal coating and ingress protection
- Forms any shape, L-shape corner, or curvature
- High brightness: 1200 nits / peak 1600 nits

Highlights

L-shape corner, or curvature

The Philips L-Line 7000 series LED panels come with a height of 25 cm and are available in 50 cm, 75 cm and 100 cm widths. These displays are ready to be installed in any landscape format with no limitations to size. Also available with bevelled corners to form curved designs in both convex and concave formats.

Active Health Monitoring

Achieve perfection through precision. Active Health Monitoring makes maintenance fast, simple, and predictable by displaying the exact item of failure and location. Utilising this software that works in real-time both online and offline, replacing the relevant part becomes an efficient process, and a must for display owners with many geographical locations.

Factory calibrated

Every Philips L-Line LED panel is calibrated in our factory under perfect circumstances. That means there's no need for further calibration on location, resulting in quicker installations. Calibration and configuration files are available to ensure fast maintenance.

Dynamic Panel Connect

Mix and match each of the Philips L-Line 7000 LED panel sizes to form a single display of any shape and dimension. Dynamic flexible

alignment pins ensure a perfect fit in any circumstance - resulting in a smooth, seamless display surface. For added convenience and efficiency, each LED panel features openings on each side to allow for versatile wired connection between the LED panels and any external input connection. Openings on the top and bottom of the LED panel can be popped out in case access is only available from the top or bottom of the panel.

Optional bevelled corners

Create bezel-free displays of any shape, size or resolution. The modular design of Philips Professional LED panels means you can adapt to any space. Build vast, immersive installations or assemble intriguing patterns. Easily create displays that flow seamlessly around doorways and other openings. Even corners and curved displays become easy to create with the new Philips 7000 series.

Perfect imagery

Your Philips Professional LED Display features built-in cable wiring to keep power and data cables tidy. Display panels are daisy-chained for both power and data, allowing you to minimise clutter and speed up installation.

Dynamic Power Saving

Philips Professional LED Displays use high-performance LEDs, which are tested thoroughly, energy efficient and cost effective. Furthermore, enhanced technology allows the display to dynamically save on power consumption.

Ingress protection

Dust, dirt, fungus and moisture resistant conformal coating protects this product and enables easier maintenance. IP30 rated and certified against ingress for reduced chance of short circuit from dust and corrosion.

Fire retardant design

Fire retardant design slows down the spread of flames in the event of fire, and help protect the structural integrity of the LED panel in case of fire. Tested and certified with European standard B1 DIN4102, British standard (BS476-7), and North-American standard UL94.

Optional easy mount brackets

Patented easy-mount brackets make installation even faster. These optional items are available for flat LED mounting, convex curved (177.5/175/172.5 degree), and L-shape 90 degree corners.

Specifications

Picture/Display

Aspect ratio: 3:1

Brightness uniformity: >=97%

Brightness after calibration: 900 nits

Brightness before calibration: 1200 nits

Calibration(brightness/color): Supported

Color temperature adjust range: 4000~9500 K (by software)

Color temperature default: 6500±500 K

Contrast ratio (typical): 3500:1

Viewing angle (horizontal): 160 degree

Viewing angle (vertical): 160 degree

Picture enhancement: Wide color gamut display

Placement: Landscape

Frame frequency (Hz): 50 & 60

Refresh rate(Hz): 2100~3900 (14 bits: 3900Hz)

Usage: Indoor

Convenience

Ease of installation: Guide pins, Light weight

Power loop through: For 230V environments: 12 cabinets or less, for 110V environments: 6 cabinets or less, 10A max

Signal control loop through: RJ45

Power

Input voltage: AC100~240V (50 & 60Hz)

Black screen power cons. (W): <10

Max. power cons. AC (W): <95

Max. power cons. BC (W): <115

Typical power cons. (W): <31.67

Operating conditions

Temperature range (operation): -20~45 °C

Temperature range (storage): -20~50 °C

Humidity range (operation)[RH]: 10~80%

Humidity range (storage) [RH]: 10~85%

Cabinet

Cabinet area (m2): 0.1875

Cabinet pixels (Dot): 32.448

Cabinet resolution (W x H): 312x104

Cabinet size (mm): 750x250x40

Data connector: RJ45

Power connector: 3 core socket (C14 in, C13 out)

Receiving card quantity: 1 pcs

Receiving card spec.: A5S plus

Receiving card brand: NovaStar

Weight (KG): 4.57 (±230g)

Cabinet diagonal (inch): 31.1"

Cabinet construction: Die-Casting Aluminum

Side angle (degree): 45

Module

LED type: SMD 1515 Copper wire

Pixel constitution: 1R1G1B

LED lifetime(Hrs): 100,000 at half brightness

Module resolution (WxH pixels): 104x104

Pixel pitch (mm): 2.4

Module size (WxH in mm): 249.9*249.9

Accessories

LAN cable (RJ45, CAT-5): 2 pcs

Power cable: 2 pcs

QSG: 1 pcs

Miscellaneous

Warranty: 2 years

Regulatory approvals: EN55032, EN55035, EN61000-3-2, EN61000-3-3, IEC/UL60950, IEC/UL62368, IEC62471, RoHS, FCC SDOC, Part 15, Class A

Fire retardancy certification: BS 476 Part7:1997, UL94, DIN4102-1

Conformal coating: hub board, backside LED module

