PHILIPS

40 inch double row LED lightbar

Ultinon Drive 5000

Off-road auxiliary lights

9800 lm, 724 m beam length

IP69K waterproof

Sturdy corrosion-free body

LUMUD5017LX1

Brilliant LED lighting for off-road adventures

Bright, durable gear for overland journeys

For drivers who demand the maximum of themselves and their machines, we offer the Philips Ultinon Drive 5000 series LED lightbars. Exceptionally rugged, with unsurpassed illumination and beam focus, advanced LED lightbars can light the way.

Greater safety with powerful brightness

- Long, bright beam for superior visibility

Durable equipment for challenging conditions

- Sturdy one-piece body for tough environments
- IP69K waterproof to master the elements
- Corrosion-free body, stainless-steel mounting brackets

Easy and flexible installation

- Accessories for simpler fitment

Ultinon Drive 5000

40 inch double row LED lightbar

LUMUD5017LX1/10

Specifications

Product description
Cable length: 1.4 m
Boost mode activation: No
Break resistance
ECE R10: No
ECE R149: No
Impact protection rating (IK): IK07
Ingress protection rating (IP): IP68 and IP69K
Installation angle: 360°
Material: Aluminium die-cast
Number of LEDs: 80x 5W
Off-road boost: No
One-piece body design
Operating temperature: -40° C to 80°C
Scratch-resistant lens
Storage Temperature: -40° C to 80°C
Technology: LED
Width: 30 inch
Boost function installation: No
Compatible with: N/A
Accessories (optional): LUMUD1007WX1
corrosion-free brackets: yes, included
Parking position light: No
Plug type: 2-pin DT Connector with 1.4m cable
Heat sink: 13-piece 1.5 mm
Fuse: No
Relay: No
Switch On/Off: No
Number of connector plugs: 1

Light characteristics
Colour temperature: 6500 K
Beam length 3 lux-m: 418 m
Beam length 1 lux-m: 724 m
Beam width 3 lux-m: 60 m
Beam width 1 lux-m: 90 m
Effective lumen output: 9800 lumen
Raw lumen output: 38080 lumen
Effective lumen output (boost): N/A

Electrical characteristics
Wattage: 145 W
Voltage: 9-36 Volt DC V

Ordering information
Order entry: UD5017LX1
GOC: 02432933

Packaging Data
EAN1: 8719018024329
EAN3: 8719018024336

Packed product information
Pack Quantity / MOQ: 1
MOQ (for professionals): 2
Box dimensions-L (mm): 1100
Box dimensions-W (mm): 110
Box dimensions-H (mm): 110
Net weight product-g: 2690
Gross weight box-g: 3140

Outer pack information
Length: 115 cm
Width: 25 cm
Height: 14 cm
Gross weight per carton: 7600 g

Highlights

Full visibility over 724 metres
The Philips UD5017L LED light bar provides an outstanding beam that illuminates the road ahead for 724 metres*. Featuring 9800 lumens (effective), our LED light bar offers ample visibility for faster reactions. As a combined spot and flood light, it shines far and wide, helping you see roadside hazards. The lamps highly homogenous beam and the cool colour temperature of 6500 Kelvin keep you focused without straining your eyes.

Sturdy one-piece body
The Philips Ultinon Drive 5000 series is built in a single piece to withstand the most challenging conditions. This allows for excellent heat management and consistently high light output throughout your journey. Rated IK07, it is shock-resistant to ensure faultless performance on and off the road. Its unbreakable polycarbonate lens can take any hit without damage or scratches, and the convenient DT connector guarantees a perfect connection.

Waterproof for durable light
With its ingenious screwless design, the Philips Ultinon Drive 5000 series can withstand the wettest conditions. IP68 and IP69K certifications mean it will perform wherever your road leads and whatever the weather. And it will be more than a match for any power washer you use to clean your car afterwards.

Corrosion-free
The Philips UD5017L LED light bar offers ultimate corrosion protection with its anodised pre-treated and automotive-grade powder-top-coat body. Its mounting brackets are made of stainless steel, which is corrosion-free. It can withstand snow, ice, and even salt. Built from durable, high-quality materials, your Philips auxiliary LED lights will provide years of reliable service.

Easy and flexible installation
Philips Ultinon Drive 5000 series are designed and tested to ensure that they function smoothly with your vehicles electrical systems. They don't create electrical interference that might interfere with other vehicle functions. Supplied with a pre-wired male/female 2-pin super seal DT connector, our LED light bars are voltage-overload and reverse-polarity protected to make installation safe and easy. Compatible with Philips UD1007W wiring harness kit for high-wattage LED light.

* *Beam length measured on 1 lux.

© 2026 Koninklijke Philips N.V.
All Rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

Issue date 2026-01-30
Version: 4.4.1

EAN: 87 19018 02432 9

www.philips.com