

# PHILIPS




Philips Unite LED  
6000 Panels

Signage Solutions

27"

Direct View LED



27HDL6400IR

## Philips Unite LED 6000 Series panels

Premium performance. Seamless integration.

The Philips Unite 6000 Series redefines professional LED performance. Purposefully engineered and expertly specified to bring ease of installation together with advanced features and stunning visual quality. Ideal for true business impact.

### **Precision calibration – colour accuracy**

- Multi-layer calibration for consistency across modules.
- Advanced colours, gradients and greyscale.
- Outstanding picture quality with real depth.

### **Flexible configurations**

- Modular design adapts to any space or resolution need.

### **Ultra-smooth picture motion**

- High refresh rates deliver flicker-free, fluid motion

### **Vivid brightness – up to 1000 nits**

- Enabling bolder visuals – even in lighter environments.

### **Brilliant COB LED + critical redundancy**

- 0.9 fine pixel pitch for ultra-sharp visuals.
- Dual power and data for fail-safe performance.
- Ideal for control rooms and high visual dependency needs.

# Highlights

### **Brilliant Flip Chip COB LED for advanced quality**

Delivering advanced quality visuals with an ultra-fine 0.7 mm pixel pitch. Vibrant colours, deep blacks and uniform brightness create an immersive visual experience, ideal for high-impact professional settings. Cool common cathodes bring stability, reliability and higher definition together with lower energy consumption for reduced cost of ownership.

### **Mission critical redundancy**

The 27HDL6500IR with 7HDL6578IM/00, and the 27HDL6400IR with 7HDL6493IM/00 Philips Unite LED 6000 Series options include built-in power and data redundancy. Providing continuous operation even during component failure, these solutions are ideal for high-stakes environments such as control rooms and broadcasting studios, where uptime is non-negotiable.

### **Ultra-smooth picture motion**

With refresh rates up to 7680 Hz, Philips Unite LED 6000 Series panels deliver flicker-free, seamless visuals. Ideal for playing fast-moving content or live feeds, and for mission-critical applications where every frame counts.

### **Vivid brightness – up to 1000 nits**

Up to 1000 nits of brightness ensure vibrant, high-contrast imagery even in areas with high ambient light. Ideal for well-lit spaces such as lobbies, shopping centres and retail spaces, or broadcasting environments that demand visual impact.

### **Precision calibration – colour accuracy**

Factory and multi-layer calibration guarantee uniform brightness and colour accuracy across all modules. The result? Consistent image quality that maintains brand integrity and professional standards at any scale. Ideal for bringing revenue-generating advertising on board. Multilayer greyscale calibration ensures flawless dark tone uniformity, vibrant colour accuracy

and ultra-smooth detail. Meanwhile, automatic recalibration keeps visuals perfect – ideal for premium LED installations.

### **Colour depth that stands out**

Higher colour depth enhances gradients, eliminates banding and brings content to life with more detail and realism. Advanced greyscale brings greater texture quality to imagery while also supporting faster processing times. Ensuring premium performance for branding perfection, unrivalled presentations and immersive displays.

### **Optimised for every environment**

Designed for flexibility, the advanced brightness control, calibration layers and performance tuning features within the Philips Unite LED 6000 Series simplify integration and operation, adapting to lighting and content needs, and delivering content without compromise. Front access makes servicing and maintenance easier, with each of the modules in a cabinet able to be removed easily, and direct access to the power supply, hub board and wiring.

# Specifications

## Picture/Display

Brightness (nits): 1000 nit  
Brightness uniformity:  $\geq 95\%$   
Calibration (brightness/colour): Brightness  
Colour temperature adjust range: 4000~9500  
(by software)  
Colour temperature default: 6500 K $\pm$ 500 K  
Contrast ratio: 5000:1  
Bit-depth (bit):  $\geq 15$   
Frame frequency (Hz): 50~60  
Refresh rate (Hz): 7680 Hz  
Colour uniformity:  $\pm 0.012$  Cx, Cy  
Colour coordinates: 0.313, 0.325 ( $\pm 0.012$  Cx, Cy)  
Viewing angle ( $^{\circ}$ ) H/V:  $>160/160$   
Scan rate: 40

## Power

Input voltage: AC100~240 V (50 and 60 Hz)  
BTU/M2: 301  
Cabinet Max Power consumption (W): 90  
Cabinet Typical Power consumption (W): 30  
Power consumption/M2 (W): 444  
Power supply unit: HWT-403V8-2S-SS

## Operating conditions

Temperature range (operation): -20 - 45  $^{\circ}$ C  
Temperature range (storage): -20 - 50  $^{\circ}$ C  
Humidity range (operation)[RH]: 10%-80% RH  
Humidity range (storage) [RH]: 10%-85% RH  
Working environment (indoor/outdoor): Indoor

## Cabinet

Cabinet area (m2): 0.2025  
Cabinet resolution (W x H): 640 x 360 pixels  
Data connector: RJ45  
Power connector: C13/C14  
Receiving card quantity: 2  
Receiving card brand: NovaStar  
Weight (kg): 4 kg ( $\pm$ )  
Cabinet construction: Die-Casting Aluminium  
Cabinet Size (W x H x D in mm):  
600 x 337.5 x 33.15  
Cabinet size (inches): 27.1"  
Receiving card type: A8s-Pro

## Module

LED type: COB  
Pixel constitution: 1R1G1B\_Flip Chip  
Pixel pitch (mm): 0.9375  
Module size (W x H in mm):  
150 x 168.75 x 2.0 mm (tolerance: +0/-0.1)  
LED Pole type: Common Cathode  
LED Lifetime (hrs, half brightness): 100,000  
Conformal coating (UV-resistant): No  
Flatness of LED module with back shell:  
 $\leq 0.25$  mm  
Module Resolution (W x H in pixels): 160 x 180  
Included: Black screen power saving, Flash  
memory, Dynamic power saving

## Miscellaneous

Warranty: 2 years  
Regulatory approvals: FCC SDOC, Part 15, Class  
A, EN55032, EN55035, EN61000-3-2, EN61000-3-  
3, IEC/UL60950, IEC/UL62368, CE, RoHS

