



Q-Line Display

Signage Solutions

55"

Direct LED Backlight

Ultra HD



55BDL3510Q

Stand out

Easy-setup 18/7 display.

Inform and enthral with a Philips Q-Line Professional Ultra HD Display. This reliable solution can be up and running as quickly as you need.

Cost-effective system solution

- Energy-saving automatic backlight control
- Integrated media player. Easily schedule USB content
- FailOver ensures content is always playing
- Easy control. Remotely manage networked displays

Effortless setup. Total control.

- Operate, monitor and maintain with CMND & Control
- Schedule what you want, when you want with SmartPlayer

Superb picture. Ultra-high brightness.

- Ultra-HD. Rich images. Stunning contrast

Highlights

CMND & Control



Run your display network over a local (LAN) connection. CMND & Control allows you to perform vital functions like controlling inputs and monitoring display status. Whether you're in charge of one screen or 100.

Integrated media player

Easily schedule content to play from USB. Your Philips Professional Display will wake from standby to play the content you want, and then return to standby once playback is done.

FailOver



From waiting room to meeting room, never show a blank screen. FailOver lets your Philips Professional Display switch automatically between primary and secondary inputs ensuring

content keeps playing even if the primary source goes down. Simply set a list of alternate inputs to be sure your business is always on.

SmartPlayer



Turn your USB into a true cost effective digital signage device. Simply save your content (video, audio, pictures) on your USB and plug into your display. Create your playlist and schedule your content via the on screen menu, and enjoy your own created playlists anytime, anywhere.

Specifications

Picture/Display

Diagonal screen size (metric): 138.7 cm
Diagonal screen size (inch): 54.6 inch
Aspect ratio: 16:9
Panel resolution: 3840 x 2160
Pixel pitch: 0.372 x 0.372 mm
Optimum resolution: 3840 x 2160 @ 60 Hz
Brightness: 400 cd/m²
Display colors: 1.07 Billion
Contrast ratio (typical): 1300:1
Dynamic contrast ratio: 500,000:1
Response time (typical): 9 ms
Viewing angle (horizontal): 178 degree
Viewing angle (vertical): 178 degree
Picture enhancement: 3/2 - 2/2 motion pull down, 3D Combfilter, 3D MA deinterlacing, Dynamic contrast enhancement, Motion compens. deinterlacing, Progressive scan
Panel technology: IPS
Clinical image: D-Image preset (dicom part 14 compatible)

Connectivity

Audio output: 3.5mm jack
Video input: DVI-I (x 1), HDMI 2.0 (x2), USB 2.0 (x2)
Audio input: 3.5 mm jack
External control: RJ45, RS232C (in/out) 2.5 mm jack, IR (in/out) 3.5 mm jack

Convenience

Placement: Landscape, Portrait
Tiled Matrix: Up to 15 x 15
Keyboard control: Lockable, Hidden

Remote control signal: Lockable

Signal loop through: RS232, IR Loopthrough
Energy saving functions: Smart Power
Network controllable: RS232, RJ45
Start-up: Switch on delay, Switch on status, Boot on source
Start-up window: enable / disable Philips logo

Sound

Built-in speakers: 2 x 10W RMS

Power

Mains power: 100 ~ 240 VAC
Consumption (Typical): 120 W
Consumption (Max): 180 W
Standby power consumption: <0.5 W
Power Saving Features: Smart Power
Energy Label Class: G

Supported Display Resolution

Computer formats: 1920 x 1080, 60Hz, 1600 x 1200, 60Hz, 1440 x 900, 60Hz, 1280 x 1024, 60Hz, 1280 x 720, 60Hz, 1280 x 800, 60Hz, 1024 x 768, 60, 70, 75Hz, 720 x 400, 70Hz, 640 x 480, 60, 67, 72, 75Hz, 1152 x 870, 75Hz, 1680 x 1050, 60Hz, 800 x 600, 56, 60, 72, 75Hz, 1152 x 864, 75Hz, 832 x 624, 75Hz
Video formats: 3840 x 2160, 60Hz, 3840 x 2160, 30Hz, 720p, 60Hz, 480i, 60Hz, 480p, 60Hz, 576i, 50Hz, 576p, 50Hz, 1080i, 50, 60Hz, 1080p, 50, 60Hz

Dimensions

Set Width: 1241.8 mm
Product weight: 16.6 kg
Set Height: 712.6 mm
Set Depth: 63.6 mm
Set Width (inch): 48.89 inch
Set Height (inch): 28.06 inch
Wall Mount: 400mm x 400mm , M6
Set Depth (inch): 2.50 inch
Bezel width: 13.9 mm (Even bezel)
Product weight (lb): 36.60 lb

Operating conditions

Altitude: 0 ~ 3000 m
Temperature range (operation): 0 ~ 40 °C
MTBF: 50,000 hour(s)
Temperature range (storage): -20 ~ 60 °C
Humidity range (operation)[RH]: 20 ~ 80% RH (No condensation)
Humidity range (storage) [RH]: 5 ~ 95% RH (No condensation)

Multimedia Applications

USB Playback Video: H.264, JPEG, MPEG, WMV3
USB Playback Picture: JPEG, BMP, PNG
USB Playback Audio: AAC, HEAAC, MPEG, WMA

Accessories

Included accessories: AC Power Cord, RS232 cable, Remote Control, Batteries for remote control, Quick start guide
Included Accessories: IR sensor cable (1.8 m) (x1), RS232 daisy-chain cable, Philips logo (x1), USB Cover and screw (x2)
Stand: BM05922(optional)

Miscellaneous

On-Screen Display Languages: English, French, German, Italian, Polish, Turkish, Russian, Simplified Chinese, Spanish, Traditional Chinese, Arabic, Japanese
Warranty: 3 year warranty
Regulatory approvals: CE, CB, BSMI, CU, EPA, ETL, FCC, Class A, VCCI

