

# PHILIPS



## LED Display

Signage Solutions

44"

Direct View LED



44BDL8139L

## Limitless

Bezel-free LED display wall.

Fill their imagination. Create seamless displays. With an L-Line Professional LED Display Wall, the possibilities are endless. The bezel-free design, wide viewing angle, and breathtaking brightness ensure authoritative imaging. At any size.

### **Immersive viewing. Versatile LED solution.**

- Perfect clarity. From broadcast studio to control room
- Ultra-high refresh rate. Smooth, judder-free images
- Ultra-thin pixel pitch of 3.9 mm. Beautiful at any size
- Ultra-thin pixel pitch of 4.8 mm. Beautiful at any size
- Create bezel-free video walls of any shape or size

### **Effortless setup. Reliable performance.**

- Join multiple cabinets to achieve higher resolution
- Built-in rear cable cover. Easy cable management
- Front-access LED modules. Easy maintenance and servicing
- High performance gold-wire LEDs
- Slim, lightweight die-cast aluminum cabinet (56 mm deep)

### **Spectacular picture. Endless possibilities.**

- Ultra-high brightness even at wide viewing angles
- Zero bezel. Create seamless display screens

## Highlights

### **LED display. Superb image**

Create bezel-free video walls of any shape, size, or resolution. The modular design of Philips Professional LED cabinets means you can adapt to any space. Build vast, immersive installations or assemble intriguing patterns. Easily create video walls that flow seamlessly around doorways and other openings.

### **Create bezel-free video walls**

Simply connect multiple LED display cabinets to create the resolution you want-whether it's 4K, 8K, or even higher. Compared to LCD screens, LED displays boast higher refresh rates that

enable smoother images. Whatever the application, you'll thrill them with crystal-clear picture quality.

### **High performance gold-wire LED**

Philips Professional LED Displays use high-performance gold-wire LEDs, which are energy-efficient and cost-effective. Light is brighter, and the LEDs last longer.

### **Front-access LED modules.**

Internal electronics are easy to access for servicing or maintenance. Each of the eight LED modules in a cabinet can be removed using a dedicated magnetic JIG tool, which lifts the module out from the front.

### **Built-in rear cable cover.**

Your Philips Professional LED Display features built-in rear cable covers to keep power and data cables tidy. Display cabinets can also be daisy-chained, for both power and data. Allowing you to minimize clutter, speed up installation.

# Specifications

## Picture/Display

Aspect ratio: 1:2  
 Brightness Uniformity:  $\geq 97\%$   
 Brightness after calibration: 800 nits  
 Brightness before calibration: 1000 nits  
 Calibration(brightness/color): Supported  
 Color temperature adjust range: 4000~9500 K (by software)  
 Color temperature default: 6500±500 K  
 Contrast ratio (typical):  $\geq 3000:1$   
 Viewing angle (horizontal): 140 degree  
 Viewing angle (vertical): 140 degree  
 Picture enhancement: Dynamic contrast enhancement, Wide color gamut display  
 Placement: Portrait  
 Frame frequency (Hz): 50 & 60  
 Refresh rate(Hz): 1200~1920  
 Usage: 24/7 Hrs, Indoor

## Convenience

Ease of installation: Guide pins, Light weight, Locking mechanism for cabinet  
 Power loop through: For 230V environments: 6 cabinets or less, for 110V environments: 3 cabinets or less  
 Signal control loop through: RJ45

## Power

Consumption (Typical):  $\leq 80$  W  
 BTU Value m2: 1,637 BTU/m2  
 Cabinet Max Power consumption: 240 W  
 Input voltage: AC200~240V/AC100-120V (50-60Hz)

## Operating conditions

Temperature range (operation): -20~45 °C  
 Temperature range (storage): -20 ~ 50 °C  
 Humidity range (operation)[RH]: 10~80%  
 Humidity range (storage) [RH]: 10~85%

## Cabinet

Cabinet area (m2): 0.5  
 Cabinet pixels ( Dot ): 32,768  
 Cabinet resolution (W x H): 128x256  
 Cabinet size (mm): 500x1000x86  
 Data connector: RJ45  
 Power connector: In/Out(C14/C13)  
 Receiving card quantity: 1 pcs  
 Receiving card spec.: A55 / A55 Plus  
 Receiving card brand: Novastar  
 Weight (KG): 15.6 kg  
 Cabinet diagonal (inch): 44  
 Cabinet construction: Aluminum+Steel

## Module

LED type: SMD 2121 Gold wire  
 Pixel constitution: 1R1G1B  
 LED lifetime(Hrs): 100,000  
 Module resolution (WxH pixels): 64x64  
 Module size (WxHxD in mm): 250\*250\*19.1  
 Pixel pitch (mm): 3.91 mm

## Accessories

Common connecting piece: 3 pcs  
 LAN cable (RJ45, CAT-5): 1 pcs (130cm)  
 QSG: 1 pcs  
 Screw bolt: 4 pcs (M10\*70) (Inner Hexagon Screw)  
 Power loop through cable: 1 pcs

## Miscellaneous

Warranty: 3 year  
 Regulatory approvals: FCC SDOC, Part 15, EMC Class A, EN55032, EN55035, EN61000-3-2, EN61000-3-3, IEC/UL60950, IEC/UL62368, IEC62471, RoHS

